

A-26581RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/22/2014

Revision date: 01/06/2015

Supersedes: 02/22/2012

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : A-26581RAM-After Fuming Dye Stain
 Product code : A-26581

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Dyestuff

1.3. Details of the supplier of the safety data sheet

Arrowhead Forensics
 11030 Strang Line Road
 Lenexa, KS 66215
 T 913-894-8388
<http://www.arrowheadforensics.com>

1.4. Emergency telephone number

Emergency number : 1.800.424.9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225
 Muta. 1B H340
 Carc. 1B H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
 H340 - May cause genetic defects
 H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical, lighting, ventilating equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P280 - Wear eye protection, protective gloves
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P370+P378 - In case of fire: Use CO2, dry chemical, foam, water spray to extinguish
 P403+P235 - Store in a well-ventilated place. Keep cool
 P405 - Store locked up
 P501 - Dispose of contents/container to local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

RAM -After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Hydrocarbons, C>=5, C5-6-rich	(CAS No) 68476-50-6	95.8	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
2-propanol	(CAS No) 67-63-0	< 3	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
methylene blue	(CAS No) 61-73-4	0.7	Acute Tox. 4 (Oral), H302
acetone	(CAS No) 67-64-1	< 0.5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
methanol	(CAS No) 67-56-1	0.194	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
distillates (petroleum), hydrotreated middle	(CAS No) 64742-46-7	0.0033 - 0.0036	Carc. 1B, H350

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

LVS650 RAM-After Fuming Dye Stain		
ACGIH	Not applicable	
OSHA	Not applicable	
2-propanol (67-63-0)		
OSHA	Not applicable	
acetone (67-64-1)		
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
methylene blue (61-73-4)		
ACGIH	Not applicable	
OSHA	Not applicable	
Hydrocarbons, C _{>=5} , C5-6-rich (68476-50-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
methanol (67-56-1)		
OSHA	Not applicable	
distillates (petroleum), hydrotreated middle (64742-46-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Gas mask. Gloves. Safety glasses.



Hand protection : Wear protective gloves.

RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Bluish liquid.
Odor	: hydrocarbon-like odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Insoluble in water. Water: Solubility in water of component(s) of the mixture : • : • : • : 2.5 g/100ml • : >= 100 g/100ml • : 2 g/100ml
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Not classified

2-propanol (67-63-0)	
LD50 oral rat	5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg bodyweight; Rat)
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
ATE US (oral)	5045.000 mg/kg body weight
ATE US (dermal)	12870.000 mg/kg body weight
ATE US (vapors)	73.000 mg/l/4h
ATE US (dust, mist)	73.000 mg/l/4h

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800.000 mg/kg body weight
ATE US (dermal)	20000.000 mg/kg body weight
ATE US (gases)	30000.000 ppmV/4h
ATE US (vapors)	71.000 mg/l/4h
ATE US (dust, mist)	71.000 mg/l/4h

methylene blue (61-73-4)	
LD50 oral rat	1180 mg/kg (Rat)
ATE US (oral)	1180.000 mg/kg body weight

methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
ATE US (oral)	100.000 mg/kg body weight
ATE US (dermal)	300.000 mg/kg body weight
ATE US (gases)	700.000 ppmV/4h
ATE US (vapors)	3.000 mg/l/4h
ATE US (dust, mist)	0.500 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Based on available data, the classification criteria are not met
Carcinogenicity : May cause cancer.

2-propanol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

2-propanol (67-63-0)	
LC50 fish 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)

acetone (67-64-1)	
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)

methylene blue (61-73-4)	
LC50 fish 1	13 mg/l (48 h; Oryzias latipes)
EC50 Daphnia 1	2.26 mg/l (48 h; Daphnia magna)
LC50 fish 2	18 mg/l (96 h; Mystus vittatus)
EC50 Daphnia 2	4.93 mg/l (24 h; Daphnia magna)
TLM fish 1	10 - 100,48 h; Poecilia reticulata

methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)

12.2. Persistence and degradability

LVS650 RAM-After Fuming Dye Stain	
Persistence and degradability	Not established.

2-propanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.40 g O ₂ /g substance
BOD (% of ThOD)	0.49 % ThOD

acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.20 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872

RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methylene blue (61-73-4)	
Persistence and degradability	Biodegradability in water: no data available. Photodegradation in the air.

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 % ThOD

12.3. Bioaccumulative potential

LVS650 RAM-After Fuming Dye Stain	
Bioaccumulative potential	Not established.

2-propanol (67-63-0)	
Log Pow	0.05 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

acetone (67-64-1)	
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

methylene blue (61-73-4)	
Log Pow	5.85 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

methanol (67-56-1)	
BCF fish 1	< 10 (72 h; Leuciscus idus)
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

2-propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)

acetone (67-64-1)	
Surface tension	0.0237 N/m

methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)

12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: UN1993 Flammable liquid, n.o.s. (Petroleum ether/Isopropyl alcohol solution) FLAMMABLE LIQUID, 3, II
UN-No.(DOT)	: UN1993

RAM-After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (DOT) : Flammable liquid, n.o.s. (Petroleum ether/Isopropyl alcohol solution)
FLAMMABLE LIQUID

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

UN-No.(IATA) : UN1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s. (Petroleum ether/Isopropyl alcohol solution)

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

LVS650 RAM-After Fuming Dye Stain

Listed on United States SARA Section 313
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45
Muta.Cat.2; R46
F; R11
Xn; R65

Full text of R-phrases: see section 16

15.2.2. National regulations

LVS650 RAM-After Fuming Dye Stain

Listed on IARC (International Agency for Research on Cancer)

RAM -After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

LVS650 RAM-After Fuming Dye Stain()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No


SECTION 16: Other information

Indication of changes	: Revision - See : *
Revision date	: 11/05/2014
Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging. Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources - heat, open flame, sparks. Avoid incompatible materials. Avoid dust creation and accumulation. Avoid inhalation and ingestion. Avoid contact with eyes. Wash thoroughly after handling.
Other information	: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Muta. 1B	Germ cell mutagenicity Category 1B
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H370	Causes damage to organs

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



RAM -After Fuming Dye Stain

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: G

SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us . However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.