Printing date: September 16, 2014

Revision: September 16, 2014

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>NIK Test K</u>
 Article number: A-800-6080 1.2 Relevant identified uses of the substance or mixture and uses advised against Opiates Reagent / Heroin and Amphetamines Test
• 1.3 Details of the supplier of the Safety Data Sheet• Manufacturer/Supplier: Safariland, LLCDistributor: Arrowhead Forensics13386 International Parkway Jacksonville, FL 3221811030 Strang Line Road Lenexa, KS 66215Customer Care (800) 347-1200(913) 894-8388; www.arrowheadforensics.com
• 1.4 Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585ARROWHEAD FORENSICS
SECTION 2: Hazards identification
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 health hazard Carc. 1A H350 May cause cancer. Corrosion Skin Corr. 1A H314 Causes severe skin burns and eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction.
· Classification according to Directive 67/548/EEC or Directive 1999/45/EC
C; Corrosive
R35: Causes severe burns.
Xn; Harmful
R40: Limited evidence of a carcinogenic effect.
Xi; Sensitising
R43: May cause sensitisation by skin contact. • Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. (Contd. on page 2)

GHS

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

literature data.

· 2.2 Label elements

· Hazard pictograms

· Signal word Danger

sulphuric acid formaldehyde · Hazard statements

P280 P264

P202

P501

(Contd. of page 1) · Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company. · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. GHS05 GHS07 GHS08 · Hazard-determining components of labelling: H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H350 May cause cancer. Precautionary statements Wear protective clothing / eye protection. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. P308+P313 IF exposed or concerned: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of water. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Restricted to professional users.

· Hazard description:

· WHMIS-symbols:

D2A - Very toxic material causing other toxic effects

E - Corrosive material



NFPA ratings (scale 0 - 4)

Health = 4Fire = 0Reactivity = 0

(Contd. on page 3)

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

(Contd. of page 2) • HMIS-ratings (scale 0 - 4) HEALTH HEALTH HEALTH HEALTH HEALTH FIRE 0 REACTIVITY Reactivity = 0 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 7664-93-9 sulphuric acid 50-00-0 formaldehyde • 2.3 Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 7664-93-9	sulphuric acid	50-100%
EINECS: 231-639-5	C R35	
Index number: 016-020-00-8	📀 Skin Corr. 1A, H314	-
CAS: 50-00-0	formaldehyde	2,5%
EINECS: 200-001-8	😡 T R23/24/25; 🧾 C R34; 🗙 Xn R40; 🗙 Xi R43	
Index number: 605-001-00-5	Carc. Cat. 3	
	line Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	-
	🚯 Carc. 2, H351	
	Skin Corr. 1B, H314	
	🚯 Skin Sens. 1, H317	

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately rinse with water.

If skin irritation is experienced, consult a doctor.

Seek immediate medical help for blistering or open wounds.

(Contd. on page 4)

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

(Contd. of page 3) · After eye contact: Protect unharmed eye. Remove contact lenses if worn, if possible. Rinse opened eye for several minutes under running water. Then consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions Strong caustic effect on skin and mucous membranes. Dizziness Coughing Breathing difficulty Nausea Hazards Danger of gastric perforation. Danger of severe eye injury. Limited evidence of a carcinogenic effect. • 4.3 Indication of any immediate medical attention and special treatment needed Contains formaldehvde. May produce an allergic reaction. Medical supervision for at least 48 hours. SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information No further relevant information available.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures For large spills, use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use limestone to neutralize and absorb spill.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Clean the affected area carefully; suitable cleaners are:

(Contd. on page 5)

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

(Contd. of page 4)

Warm water

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Use only in well ventilated areas.

When diluting always pour product into water and not vice versa.

· Information about fire - and explosion protection: No special measures required.

\cdot 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from metals.

Do not store together with alkalis (caustic solutions).

Protect from humidity and water.

• Further information about storage conditions: Keep container tightly sealed.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
7664-93-9 st	Ilphuric acid	
IOELV (EU)	Long-term value: 0,05 mg/m ³	
PEL (USA)	Long-term value: 1 mg/m ³	
REL (USA)	Long-term value: 1 mg/m ³	
TLV (USA)	Long-term value: 0,2* mg/m³ *as thoracic fraction	
EL (Canada)	Long-term value: 0,2 mg/m³ ACGIH A2; IARC 1	
EV (Canada)	Long-term value: 0,2 mg/m ³	
		(Contd. on page 6)

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

PEL (USA) Short-term value: 2 ppm Long-term value: 0,75 ppm see 29 CFR 1910, 1048(c) REL (USA) Long-term value: 0,016 ppm Ceiling limit: 0.1* ppm '15-min; See Pocket Guide App. A Ceiling limit: 0.3* mg/m³. 0,3 ppm (SEN) NIC-DSEN; RSEN EL (Canada) Long-term value: 0,3 ppm Ceiling limit: 1,5 ppm DNELs No further relevant information available. PNCCs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further n quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material The exact beak through time has to be found out by the manufacturer of the protective gloves and checked prior to the application.	50-00-0 form	(Contd. of page
see 29 CFR 1910,1048(c) REL (USA) Long-term value: 0,016 ppm Ceiling limit: 0,1* ppm *15-min; See Pocket Guide App. A TLV (USA) Ceiling limit: 0,3 mg/m³, 0,3 ppm (SEN) NIC-DSEN; RSEN EL (Canada) Long-term value: 0,3 ppm Ceiling limit: 1, ppm ACGIH A2; IARC 1; S EV (Canada) Short-term value: 1,0 ppm Ceiling limit: 1,5 ppm DNELS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be im		Short-term value: 2 ppm
Ceiling limit: 0,1* ppm 115-min; See Pocket Guide App. A TLV (USA) Ceiling limit: 0,37 mg/m³, 0,3 ppm (SEN) NIC-DSEN; RSEN EL (Canada) Long-term value: 0,3 ppm Ceiling limit: 1,5 ppm Oxeling limit: 1,5 ppm DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from 6odStuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / times / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protection may be advisable. Vas suitable respiratory protective device when aerosol or mist is formed. Protection of hands: Protection of hands: Matrei dof gloves		
115-min; See Pocket Guide App. A TLV (USA) Ceiling limit: 0,37 mg/m³, 0,3 ppm (SEN) NIC-DSEN; RSEN EL (Canada) Long-term value: 0,3 ppm Ceiling limit: 1 ppm ACGIH A2; IARC 1; S EV (Canada) Short-term value: 1,0 ppm Ceiling limit: 1,5 pm DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For splis, respiratory protection may be advisable. Use suitable respiratory protection may be advisable. Use suitable respiratory protection may be advisable. Use suitable respiratory protection of hands: Wash lands of gloves Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of th	REL (USA)	
TLV (USA) Ceiling limit: 0.37 mg/m³, 0.3 ppm (SEN) NIC-DSEN; RSEN EL (Canada) Long-term value: 0.3 ppm Ceiling limit: 1 ppm ACGIH A2; IARC 1; S EV (canada) Short-term value: 1,0 ppm DNELs No further relevant information available. PMECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Protective device device when aerosol or mist is formed. Portective gloves Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance an		
EL (Canada) (SEN) NIC-DSEN; RSEN EL (Canada) Long-term value: 0,3 ppm Ceiling limit: 1, ppm ACGIH A2; IARC 1; S Short-term value: 1,0 ppm Ceiling limit: 1, 5 ppm DNELs No further relevant information available. PMECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / furmes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation a clegradation. Material of gloves The selection of the suitabl		
EL (Canada) Long-term value: 0,3 ppm Ceiling limit: 1 ppm ACGIH A2; IARC 1; S EV (Canada) Short-term value: 1,0 ppm Ceiling limit 1,5 ppm DNELs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: Mathematical protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protective device when aerosol or mist is formed. Protection of hands: Wash ender sepiratory protective device when aerosol or mist is formed. Protection of hands: Material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and	TLV (USA)	
Ceiling limit: 1 ppm ACGIH A2; IARC 1; S EV (Canada) Short-term value: 1,0 ppm Ceiling limit: 1,5 ppm DNELs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on furthe	EL (Canada)	
EV (Canada) Short-term value: 1,0 ppm Ceiling limit 1,5 ppm DNELs No further relevant information available. PNECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protection of hands: Vov Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Material	(• • • • • • • • • • • • • •	
Ceiling limit 1,5 ppm DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further n quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and		
DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Preteration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and	. ,	
 PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective end hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further may and y avies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and substances. 	Ceiling limit	1,5 ppm
Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Pertention time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and		
 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparate selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and the glove material or use the product is a preparation of protection.		
Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. Protection of hands:	Auditional in	Tormation. The lists valid during the making were used as basis.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparat Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further m quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and	Wash hands I Do not inhale Avoid contact Respiratory Not required u For spills, res Use suitable r Protection of	before breaks and at the end of work. gases / fumes / aerosols. with the eyes and skin. protection: under normal conditions of use. piratory protection may be advisable. respiratory protective device when aerosol or mist is formed.
Selection of the glove material on consideration of the penetration times, rates of diffusion a degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefore checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and	Prote	ective gloves
quality and varies from manufacturer to manufacturer. As the product is a preparation of substances, the resistance of the glove material can not be calculated in advance and has therefor checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and	Selection of degradation. Material of g	the glove material on consideration of the penetration times, rates of diffusion and th loves
The exact break through time has to be found out by the manufacturer of the protective gloves and	quality and v substances, t checked prior	varies from manufacturer to manufacturer. As the product is a preparation of seve he resistance of the glove material can not be calculated in advance and has therefore to to the application.
	be observed.	(Contd. on page

(Contd. on page 7)

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

(Contd. of page 6)

Eye protection:

Contact lenses should not be worn.



Safety glasses

 Body protection: Protective work clothing
 Limitation and supervision of exposure into the environment No further relevant information available.

· Risk management measures

See Section 7 for additional information. No further relevant information available.

SECTION 9: Physical and chemical properties

SECTION 9: Physical and chemical properties			
 9.1 Information on basic physical ar General Information Appearance: Form: Colour: Odour: Odour threshold: 	nd chemical properties Liquid Colourless Acrid Not determined.		
pH-value at 20 °C:	< 1		
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not Determined. 212 °F / 100 °C		
· Flash point:	Not applicable.		
[•] Flammability (solid, gaseous):	Not applicable.		
· Auto/Self-ignition temperature:	Not determined.		
Decomposition temperature:	Not determined.		
· Self-igniting:	Product is not self-igniting.		
· Danger of explosion:	Product does not present an explosion hazard.		
 Explosion limits: Lower: Upper: 	Not determined. Not determined.		
· Vapour pressure:	Not determined.		
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1,76 g/cm ³ Not determined. Not determined. Not determined.	(Contd. on page 8)	

(Contd. of page 7)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

 Solubility in / Miscibility with water:

Soluble.

· Partition coefficient (n-octanol/water): Not determined.

 Viscosity: Dynamic: Kinematic:
 9.2 Other information

Not determined. Not determined. No further relevant information available.

SECTION 10: Stability and reactivity

[•] 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with alkali (lyes).

Corrosive action on metals.

Reacts with metals forming hydrogen.

Toxic fumes may be released if heated above the decomposition point.

Heating occurs when water is added.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• **10.6 Hazardous decomposition products:** Sulphur oxides (SOx)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity:

· LD/LC50 values relevant for classification:

50-00-0 formaldehyde

Oral LD50 >200 mg/kg (rat)

Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

• on the eye: Strong caustic effect.

• Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Corrosive Irritant Danger through skin adsorption. Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

May cause cancer.

(Contd. on page 9)

(Contd. of page 8)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

• Sensitisation: Sensitization possible by skin contact.

· Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

- Repeated exposures may result in skin and/or respiratory sensitivity.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 1A

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- **Remark:** After neutralization a reduction of the harming action may be recognized
- · Additional ecological information:

· General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Danger to drinking water if even small quantities leak into the ground.

Must not reach sewage water or drainage ditch undiluted or unneutralized.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· 12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dilute concentrate with water and neutralize afterwards with suitable alkali material (sodium hydroxide solution, lime). The formed neutral salts are relatively environment-friendly.

Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Contd. on page 10)

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

(Contd. of page 9)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	on	
· 14.1 UN-Number		
· DOT, ADR, IMDG, IATA	UN1830	
· 14.2 UN proper shipping name		
DOT	Sulfuric acid	
	1830 SULPHURIC ACID	
 IMDG, IATA 14.3 Transport hazard class(es) 	SULPHURIC ACID	
• • • • •		
DOT		
<u> <u> </u></u>		
· Class	8 Corrosive substances.	
[·] Label	8	
· ADR		
· Class	8 (C1) Corrosive substances.	
· Label	8	
· IMDG, IATA		
· Class	8 Corrosive substances.	
· Label	8	
· 14.4 Packing group		
DOT, ADR, IMDG, IATA	II	
14.5 Environmental hazards:		
Marine pollutant:	No	
• 14.6 Special precautions for user	Warning: Corrosive substances.	
 Danger code (Kemler): EMS Number: 	80 E A S B	
	F-A,S-B Acids	
 Segregation groups 14.7 Transport in bulk according to Anno 		
MARPOL73/78 and the IBC Code	Not applicable.	
		(Contd. on page

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

	(Contd. of page 10)
· Transport/Additional information:	
· ADR	
 Limited quantities (LQ) 	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
• Transport category	2
Tunnel restriction code	E
• UN "Model Regulation":	UN1830, SULPHURIC ACID, 8, II

SECTION 15: Regulatory information

United States (USA) SARA	
Section 355 (extremely hazardous substances):	
7664-93-9 sulphuric acid	
50-00-0 formaldehyde	
Section 313 (Specific toxic chemical listings):	
7664-93-9 sulphuric acid	
50-00-0 formaldehyde	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65 (California):	
Chemicals known to cause cancer:	
50-00-0 formaldehyde	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic Categories	
EPA (Environmental Protection Agency)	
50-00-0 formaldehyde	
IARC (International Agency for Research on Cancer)	
7664-93-9 sulphuric acid	
50-00-0 formaldehyde	

(Contd. of page 11)

A2

A2

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: September 16, 2014

Revision: September 16, 2014

Trade name: NIK Test K

 TLV (Threshold Limit Value established by ACGIH) 	
7664-93-9 sulphuric acid	

50-00-0 formaldehyde

· NIOSH-Ca (National Institute for Occupational Safety and Health)

50-00-0 formaldehyde

· Canada

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

50-00-0 formaldehyde

· Canadian Ingredient Disclosure list (limit 1%)

7664-93-9 sulphuric acid

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H331 Toxic if inhaled.
- H351 Suspected of causing cancer.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

- R34 Causes burns.
- R35 Causes severe burns.
- R40 Limited evidence of a carcinogenic effect.
- R43 May cause sensitisation by skin contact.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 13)

Printing date: September 16, 2014

Website: www.chemtelinc.com

Revision: September 16, 2014

Trade name: NIK Test K

(Contd. of page 12) ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Acute Tox. 3: Acute toxicity, Hazard Category 3 Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Carc. 1A: Carcinogenicity, Hazard Category 1A Carc. 2: Carcinogenicity, Hazard Category 2 · Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573