NARK20034 Hemp CBD Detection Test

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/26/2020

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : NARK20034 Hemp CBD Detection Test

Product code : NARK20034

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

SIRCHIE
100 Hunter Place
Youngsville, NC 27596 - USA
T 919-554-2244; 800-356-7311 - F 919-554-2266; 800-899-8181
http://www.sirchie.com

1.4. Emergency telephone number

Emergency number : 1.800.424.9300 (USA) +1-703-527-3887 (INTL)
CHEMTREC: 1.800.424.9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapour
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 - Take precautionary measures against static discharge.
P264 - Wash hands thoroughly after handling.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, ABC-powder, dry sand to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
ethanol	(CAS-No.) 64-17-5	90.4 - 18	Flam. Liq. 2, H225
sodium hydroxide	(CAS-No.) 1310-73-2	0.4 - 2.4	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314
Proprietary component		<= 1.6	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove the victim into fresh air.

First-aid measures after skin contact : Wash immediately with lots of water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : Rinse mouth with water. Do not induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : ABC powder. Alcohol-resistant foam. Dry sand.

Unsuitable extinguishing media : Water.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Gloves.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container closed when not in use. Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm

Proprietary component
Not applicable

sodium hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Mixture contains one or more component(s) which have the following colour(s):
Colourless White

Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour:
Alcohol odour Pleasant odour Odourless

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : No data available

Vapor pressure : No data available

Relative vapor density at 20 °C : No data available

Relative density : No data available

Solubility : No data available

Log Pow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosion limits : No data available

Explosive properties : No data available

Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

sodium hydroxide (1310-73-2)	
ATE US (oral)	500 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

ethanol (64-17-5)	
Additional information	Ethyl alcohol (200 Proof) has been shown to cause cancer in Human and Animals when ingested in volume over time. There is no link to cancer in limited exposure scenarios.

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

ethanol (64-17-5)	
LC50 fish 1	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

sodium hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%)

sodium hydroxide (1310-73-2)	
EC50 Daphnia 1	40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration)

12.2. Persistence and degradability

ethanol (64-17-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O_2/g substance
Chemical oxygen demand (COD)	1.7 g O_2/g substance
ThOD	2.1 g O_2/g substance
BOD (% of ThOD)	0.43

sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

ethanol (64-17-5)	
BCF fish 1	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.

sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Log Koc	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

sodium hydroxide (1310-73-2)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1170 Ethanol solutions, 3, II
UN-No.(DOT) : UN1170
Proper Shipping Name (DOT) : Ethanol solutions
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx)	:	242
DOT Special Provisions (49 CFR 172.102)	:	24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	4b;150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	:	127
Other information	:	No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG)	:	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II
UN-No. (IMDG)	:	1170
Proper Shipping Name (IMDG)	:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Class (IMDG)	:	3 - Flammable liquids
Packing group (IMDG)	:	II - substances presenting medium danger
Limited quantities (IMDG)	:	1 L

Air transport

Transport document description (IATA)	:	UN 1170 Ethanol solution, 3, II
UN-No. (IATA)	:	1170
Proper Shipping Name (IATA)	:	Ethanol solution
Class (IATA)	:	3 - Flammable Liquids
Packing group (IATA)	:	II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation

SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us . However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.